



RESISTANCE @ +25°C = 5,000,000 Ω ± 10%  
 RESISTANCE/TEMPERATURE CURVE = "Y"  
 BETA "β" (0 TO +50°C) = 4,640°K NOMINAL  
 TEMPERATURE COEFFICIENT @ +25°C = -5.22%/°C NOMINAL  
 DISSIPATION CONSTANT = 2 mW/°C NOMINAL (STILL AIR)  
 THERMAL TIME CONSTANT = 5 SECONDS NOMINAL (STILL AIR)  
 THERMAL TIME CONSTANT = 0.5 SECONDS NOMINAL (WELL STIRRED OIL)  
 MAXIMUM TEMPERATURE RATING = +300°C

|      |                       |          |     |
|------|-----------------------|----------|-----|
| NONE | RELEASE TO PRODUCTION | 01/28/14 | DD  |
| REV  | REVISION RECORD       | DATE     | APP |

|                         |  |
|-------------------------|--|
| SCALE NONE              | © COPYRIGHT<br><b>U.S. SENSOR CORP.</b><br>714-639-1000 www.ussensor.com<br><b>NTC THERMISTOR</b><br>P/N 505YG7K |
| DRAWN BY<br>DAN DANKERT |  |
| DATE 01/28/14           |  |
| REV. NONE               |  |
| LAYER 0 OF 1            |  |