

Alpha[®] 800-2.4



Product Specifications

Caliper (mils/ µm)	Basis Weight	Brightness (UV Included)	Thermal Response - Nominal				Gurley Stiffness Nominal (mg)		Elmendorf Tear Nominal (g)		Parker Print Surf
			Static - (°C ± 5°)		Dynamic - Atlantek 400 (mJ/mm ²)		MD:	CD:	MD:	CD:	
			0.2 ODU	87	0.2 ODU	4.6					
2.40 ± 0.15/61 ± 5	17 x 22— 500 (lbs)	>85	0.2 ODU	87	0.2 ODU	4.6	28	15	31	35	<1.90
	13.6 ± 0.7		1.0 ODU	134	1.0 ODU	7.9					
	g/m ²		Max. Density	1.38	Max. Density	1.78					
	51.1 ± 2.7		Required Temp.	149	Energy Req.	14.6					

Features:

- 800-sensitivity
- Excellent graphics and bar code imaging
- Bright white appearance
- Flexographic printable front and back
- Lithographic printable back side only

Ideal For:

- Point-of-sale receipts
- ATM receipts
- Kiosks
- Parking receipts
- Airline check-in kiosks
- High speed facsimile
- Charting
- Portable receipts

Environmental Characteristics:

- Produced without the use of bisphenol A (BPA)

