





High Power BTE

Model	KE388-DWH	KE288-DWH
Device Configurations		
Battery size	13 Zinc-Air	
IP Classification	IP 68	
Control Option	Telecoil, DAI	
Audiological Features		
WARP compression (WDRC) - number of channels	8	6
Soft Switching	●	●
Multiscope Adaptive Directionality	●	
Adaptive Directionality		●
Environmental Classifier	●	●
DFS Ultra II	●	●
Noise Tracker II	●	●
Wind Guard	●	●
Expansion	●	●
Synchronized Acceptance Manager	●	
Tinnitus Sound Generator	●	●
Functional Features		
Synchronized Push Button	●	
Synchronized Volume Control	●	
Volume Control	●	●
Phone Now	●	●
Comfort Phone	●	
Direct audio streaming (MFi, Android™*)	●	
ReSound TV Streamer 2, Remote Control, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●
ReSound Smart 3D™ app	●	●
ReSound Assist		
Remote Fine Tuning	●	●
ReSound Assist Live	●	●
Remote Firmware Updates	●	●
Fitting Features		
Fitting Software ReSound Smart Fit™ 1.10 or higher	●	●
Fully Flexible Programs	4	4
Auto DFS	●	●
Onboard Analyzer II	●	●
Wireless Fitting with Noahlink Wireless	●	●



* Compatible with Android smartphones that support direct Android streaming to hearing aids



© 2020 GN Hearing A/S. All rights reserved. ReSound is a trademark of GN Hearing A/S. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the US and other countries. Android is a trademark of Google LLC. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.

Technical specifications

KE88-DWH

IEC 60118-0: 1983_AMD1:1994
IEC 60118-0:2015 (*)
IEC 711 Ear Simulator

ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler



Reference test gain (60 dB SPL input)	1600 Hz/HFA	60	53	dB
Full-on gain (50 dB SPL input)	Max.	80	73	dB
	1600 Hz/HFA	73	67	
Maximum output (90 dB SPL input)	Max.	141	134	dB SPL
	1600 Hz/HFA	135	130	
Total harmonic distortion	500 Hz	1.4	2.8	%
	800 Hz	0.6	0.4	
	1600 Hz	0.8	0.4	
	3200 Hz	-	0.1	
Telecoil sensitivity (1 mA/m input)	Max.	110	103	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	123	114	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	104	98	
Equivalent input noise, w/o noise reduction		23	22	dB SPL
1/3 Octave equivalent input noise, w/o Noise reduction	1600 Hz	13	12	dB SPL
Frequency range IEC 60118-0: 2015		100-5270*	100-4940	Hz
Current Drain (Quiescent/Operating)		1.18/1.4	1.18/1.4	mA
Weight of hearing aid (without hook, tube and dome/earmold)		4.35 / 0.15		gram/oz

* Measured according to IEC60118-0:2015, with 711 Ear Simulator coupler.




IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator

ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler

Patents pending



All specifications are subject to change without notice



401443014CA-20.11-Rev.A