



A CSW Industrials Company

# CALCI-FREE™

Tankless Water Heater Flush

# **Description**

Calci-free Tankless Water Heater Flush is an efficient chemical cleaner designed for tankless water heaters found in commercial and residential applications. It contains a unique combination of organic and inorganic cleaners, as well as patented corrosion inhibitors.

# **Applications**

Any type of tankless water heater. Do not use on aluminum.

#### **DIRECTIONS FOR USE:**

#### **NOT FOR USE ON ALUMINUM**

- 1. Turn off power source (electricity & gas) to the tankless water heater.
- 2. Shut off main water supply valve to tankless water heater.
- 3. Close hot and cold water isolation valves.
- 4. Clean cold water inlet screen of any sediment or dirt.
- 5. Using the Calci-free Flush Kit Bucket, add and mix full contents of Calci-free™ into two gallons of water until completely dissolved.
- 6. Connect end of one hose to pump's discharge connection and the other end of same hose to the cold isolation valve on the tankless water heater.
- 7. Connect the second hose to the hot isolation valve on the tankless water heater and place the other end of the hose directly into the bucket.
- 8. Place strainer at the bottom of the pail and then place pump on strainer.
- 9. Open hot and cold isolation valves.
- 10. Turn on pump and allow solution to recirculate 20 minutes. Follow manufacturer's service manual for specific cleaning instructions.
- 11. After cleaning is completed, turn off pump.
- 12. Close cold isolation valve and remove hose from valve.
- 13. Remove pump from the bucket. Dispose of used cleaning solution in accordance with local regulations.
- 14. Replace the end of the hose already connected to the hot water isolation valve into bucket.
- 15. Open main water supply valve to tankless water heater and allow cold water to circulate through water heater into bucket for 5 minutes (empty bucket as needed).
- 16. Close hot isolation valve and remove hose.
- 17. Reconnect power source (electricity & gas).

## READ SDS AND ALL DIRECTIONS FOR USE, HAZARD AND PRECAUTIONARY STATEMENTS ON LABEL BEFORE USING.



#### **Characteristics | Features**

- Thorough Cleaning
- Cleans Circulation Coils
- Fast Acting
- Restores Water Flow & Pressure
- Easy to Use
- · No Strong Odor

## **Packaging**

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
68708	1.2 lbs (544.3 g) - Refill	12	16	.46
68711	Calci-free Kit	1	13	.68

# **Specifications**

Appearance Solid mixture

Shelf Life 2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



## **Precautionary Statements**

Refer to Safety Data Sheet (SDS).

### **KEEP OUT OF REACH OF CHILDREN**

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

## **Limited Warranty**



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

## RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com 3255 Wyandotte St. East • Windsor, ON NBY 1E9, Canada • 519-966-4901 PO Box 5266 • Brendale, Qld 4500, Australia • 1300 77 2878 • rectorseal.com.au

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2022 RectorSeal. All rights reserved. R50000-0422