



A GSW Industrials Company

PRODUCT DATA SHEET

LIQUIDDRAIN™
Acid-Free Drain Cleaner

Description

LiquidDrain™ is a commercial strength, non-acid, and non-flammable drain opener. LiquidDrain’s penetrating surfactant foaming action lifts and pushes contaminants off to rapidly clear drain, sewer, or waste line. LiquidDrain penetrates the grease.

Characteristics | Features

- Non-flammable
- Non-acid
- Commercial strength
- Odor-free
- Non-hazardous

Applications

LiquidDrain™ lifts and pushes contaminants off to clear drain, sewer, or waste line. This includes paper, rags, sanitary products, sludge, soap, fat, wood, hair, food, and difficult-to-remove cooking grease found in or near restaurants. LiquidDrain penetrates the grease. LiquidDrain may be used on cast iron, steel, copper, brass, lead, and plastic pipe.

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
80391	1 U.S. Quart Bottle	12	24	0.90

Instructions

READ ALL DIRECTIONS, SDS AND WARNINGS ON LABEL BEFORE USING

For general drains, pour 16 ounces into the drain, allow to work 15-20 minutes, flush with warm water and repeat if necessary. For larger drains, use entire contents, allow to work 30 minutes, and flush with warm water. To maintain drains, use 8 ounces for residential or 16 ounces for commercial drains weekly.

For additional technical information, call Toll Free 1-800-231-3345

Precautions

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**



**DANGER!  POISON!
CAUSES SEVERE BURNS.
MAY BE FATAL IF SWALLOWED OR INHALED – KEEP OUT OF REACH OF CHILDREN
READ BACK PANEL CAREFULLY.**

CONTAINS: Sodium Hydroxide. Do not get in eyes, on skin, or on clothing. Wear goggles and rubber gloves. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse.

FIRST AID: Eyes - Hold eyes open and rinse gently with water for 15 minutes. **Skin** - Remove contaminated clothing immediately. Rinse skin with plenty of water for 15 minutes. **Ingestion - Do not induce vomiting.** Only if conscious, give large amount of water. **Use with adequate ventilation.**

For additional information, refer to Safety Data Sheet.

Specifications

Wt/Gal @ 77°F	10.3+-0.5 lbs/ gal.
Flash Point SETA CC	None
Color	Blue
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055 USA
713-263-8001 • Fax 713-263-7577
Toll-free 800-231-3345 • Fax 800-441-0051

RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice.