



A CSW Industrials Company

# PRODUCT DATA SHEET

## PLUMBER'S GREASE

Lubrication for faucets and stem valves

### Description

RectorSeal Plumber's Grease is a all-purpose grease for lubricating metal parts of faucets, stems and valves in service up to 180°F. Meets Mil-G 10924 C Specifications.



### Applications

RectorSeal Plumber's Grease is formulated for many plumbing applications. Makes hard turning faucets work smoothly. Lubricates stems of faucets, valves and ballcocks and prevents corrosion.

- Faucets
- Ballcock linkages
- Valve stems
- other plumbing applications

### Characteristics | Features

- Easy to apply
- Service temperature up to 180°F
- Meets Mil-G 10924 C Specifications

### Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
50811	2 fl. oz. (29 mL)	12	2	0.19

## Instructions

Apply RectorSeal Plumber's Grease on are to be lubricated and assemble components.

For additional technical information, call toll free 1-800-231-3345.

## Precautions

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

**Contains: Lubricating grease.** Wash after handling. Do not take internally **FIRST AID:** For any overexposure, get immediate medical attention after first aid is given. **EYES**—Hold eyes open and rinse gently with water. **SKIN**—Wash with soap and water. **INGESTION**—Only if conscious, give large amounts of water and **DO NOT INDUCE VOMITING. FIRE AND SPILLS:** Use water fog, CO<sub>2</sub>, foam, or dry chemicals. Wipe up spills to prevent footing hazard. **STORAGE AND HANDLING:** Store in cool, well-ventilated area. Keep container closed. Do not reuse empty container.

**KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet.

## Specifications

Specific gravity (H <sub>2</sub> O=1)	2.0.
VOC	0 g/L
Flash Point SETA CC	300°F (149°C)
Color	amber
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by **RectorSeal® LLC • 2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2018 RectorSeal. All rights reserved. R50289-0718