



A CSW Industrials Company

PRODUCT DATA SHEET

8-WAY™ Boiler Water Conditioner

Description

8-WAY is a complete boiler water treatment for steam and hot water systems. Removes sludge and rust scale, inhibits boiler corrosion, steam line corrosion and lime scale. Prevents oxygen pitting, surging and foaming. Controls pH with color indicator.

Applications

8-Way is a protective maintenance for steam and hot water heating systems. Recommended for cleaning very dirty steam boilers, boilers with excessive scale, rust and must. 8-Way can be used to maintain clean, rust free water on new or existing systems.

Instructions for Use

READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

Steam Boiler (1) Pour or pump 8-Way into boiler until water turns violet in color. One quart typically treats up to 30 gallons water content - approximately 600 sq. ft. of radiation, or 5.5B.H.P. (2) Allow to steam for 1/2 to 3 hours, then drain and flush. (3) Refill boiler water and add 1 qt. of 8-way for each qt. originally used. 8-Way remains in the system to inhibit surging and corrosion. **New Steam Boiler** installation, add 8-way until water turns blue or violet. Leave in system to condition water for one full season. **Hot Water Boiler** use 1 qt 8-way for each 25 gallons of circulating water. **Sure-cure color indicator** - Light blue green (insufficient dosage) Violet (cleaning dosage) Blue or Violet (scale prevention dosage).

For additional technical information, call Toll Free 1-800-231-3345



Characteristics | Features

- Builds alkalinity
- Controls pH
- Inhibits corrosion
- Sure-cure color indicator

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
68712	Quart (.946 l)	12	31	0.71
68714	Gallon (3.79 l)	4	42	1.27
68716	30 Gallons (113.5 l)	1	296	NA

Specifications

Wt/Gal @ 77°F	9.2 lbs/gal
Flash Point SETA CC	None
Color	Dark blue or purple liquid
Shelf Life	3 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances



DANGER!

Causes severe skin burns and serious eye damage.

May be harmful if swallowed.

May be corrosive to metals.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300.

Contains: Sodium Hydroxide 1310-73-2, Sodium Nitrite 7632-00-0, Sodium Phosphate 68915-31-1, Water 7732-18-5. May cause respiratory irritation. May cause cancer. Very toxic to aquatic life.

Precautionary Statements - PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. **RESPONSE: IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. **IF IN EYES:** Rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. **IF EXPOSED OR CONCERNED:** Get medical advice/attention. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. **STORAGE:** Store locked up. Store in corrosive resistant stainless steel container with a resistant inner liner. **DISPOSAL:** Dispose of contents/ container to an approved waste disposal plant. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50490-0720