



BUZ-AWF™

WASP AND HORNET KILLER SPRAY

DESCRIPTION

BUZ-AWF™ is a wasp, hornet, yellow jacket and bee killer. It shoots a 20-foot stream. It is designed to help protect the service technician when working on electrical boxes, outdoor condensing units, cooling towers, air handlers and any other equipment which may become a nesting place.

CHARACTERISTICS

- * High pressure, long distance spray.
- * EPA Registered
E.P.A. REG. NO. 3862-174-51219
E.P.A. EST. NO. 9143-TX-1
- * Non-conductive up to 47KV.
- * Kills wasps, hornets, yellow jackets and bees.
- * Shoots 20 foot stream.

APPLICATIONS

BUZ-AWF™ kills wasps, hornets, yellow jackets and bees. It shoots a 20-foot stream, allowing the operator to stay back from places being sprayed.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
84390	16 ounce aerosol	12	13	0.57

BUZ-AWF™ WASP AND HORNET KILLER SPRAY

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

It is a violation of Federal law to use this product in manner inconsistent with its labeling. Read Entire Label. Do not use in commercial food/feed handling establishments, restaurants or other sites where food/feed is commercially prepared, processed or served. Not for use in Federally inspected meat and poultry plants.

- It is preferable to apply BUZ-AWF™ in the evening after all the insects have returned to the nest.
- Aim valve opening at nest and depress button with wind at your back.
- Continue spraying until the nest is soaked with the spray.
- Wait 24 hours before removing nest.
- Repeat as necessary

Do not apply to pets or contaminate feed, foodstuffs, dishes or utensils. Avoid spraying vegetation directly.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

CAUTION

**KEEP OUT OF REACH OF CHILDREN
PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

CAUTION: Causes eye irritation. Avoid contact with eyes or clothing. Wash thoroughly with soap and water after handling. Prolonged or frequently repeated skin contact may cause allergic reaction some individuals

ENVIRONMENTAL HAZARDS

This product is toxic to fish and other aquatic invertebrates. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

Contents under pressure. Keep away from heat, sparks, and open flame. Do not puncture or incinerate container. Exposure to temperature above 130° F may cause bursting.

STORAGE & DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Storage: Do not store near heat or open flame. Store in cool dry area away from children.

Disposal: Do not puncture or incinerate. **If empty:** Place in trash or offer for recycling if **available**. **If partly filled:** Call your local solid waste agency or 1-800-CLEANUP for disposal instructions.

FIRST AID

IF IN EYES: Hold eyes open and rinse slowly and gently with water 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

IF SWALLOWED: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN: Contains petroleum distillate - vomiting may cause aspiration pneumonia.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	6.67 lbs/gal
Flash Point SETA CC	152° F (67° C)
Color	Clear amber liquid
Shelf Life	2 years minimum, subject to inspection.

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

RectorSeal makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal shall not be liable for incidental or consequential damages.

MANUFACTURED FOR

RectorSeal • 2601 Spenwick Drive • Houston, Texas 77055-1035

Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051

www.rectorseal.com