



A CSW Industrials Company

PRODUCT DATA SHEET

BUZ-AWF™

Wasp and Hornet Killer Spray

Description

BUZ-AWF is a wasp, hornet, yellow jacket and bee killer. It shoots a 20-foot stream. It is designed to help protect the service technician when working on electrical boxes, outdoor condensing units, cooling towers, air handlers and any other equipment which may become a nesting place.

Applications

BUZ-AWF kills wasps, hornets, yellow jackets and bees. It shoots a 20-foot stream, allowing the operator to stay back from places being sprayed.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Read entire label. Do not use in commercial food/feed handling establishments, restaurants or other sites where food/feed is commercially prepared, processed or served. Do not apply this product in a way that will contact workers or other persons, either directly or through drift; only protected handlers may be in the area during application. May cause staining (darkening) of asphalt surfaces and shingles.

For best results, spray in early morning or late evening when insect activity is minimal. Stand a safe distance from the nest and not directly underneath. Remove protective cap. Hold can upright and point spray opening toward nest with wind at your back. Spray until nest is thoroughly saturated to kill the entire nest population. Residual action will kill wasps and hornets returning to the nest.

Wait at least 24 hours before removing the nest. To kill wasps, hornets, yellow jackets and bees on the outdoor surfaces of eaves, screens, window frames, doors, patios, cracks, holes or crevices wherever insects are noticed, spray for about 1-2 seconds or until surfaces are moist. To prevent entrance of insects into the house, spray around points where insects enter such as outside plumbing, faucets, etc., and cracks or crevices in foundation as well as along sills and ledges. • All outdoor applications must be limited to spot or crack and crevice treatment only.

- Do not apply to pets.
- Do not apply when food is present.
- Avoid spraying vegetation directly.

For additional technical information, call Toll Free 1-800-231-3345



Characteristics | Features

- Sprays up to 20 ft.
- Kills on contact
- Dielectric breakdown 47,300 volts
- EPA Reg. No. 3862-174-51219

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
84390	16 ounce aerosol	12	13	0.57

BUZ-AWF™

Wasp and Hornet Killer Spray

Specifications

Wt/Gal @ 77°F	6.67 lbs/gal
Flash Point SETA CC	152°F (67°C)
Color	Clear amber liquid
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

CAUTION!

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300.

Refer to Safety Data Sheet (SDS) for precautionary statements

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured for

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50744-1120