



A CSW Industrials Company

PRODUCT DATA SHEET

CALCI-FREE™ Tankless Water Heater Flush

Description

Calci-Free Tankless Water Heater Flush is an efficient chemical cleaner designed for tankless water heaters found in commercial and residential applications. It contains a unique combination of organic and inorganic cleaners, as well as patented corrosion inhibitors.

DIRECTIONS FOR USE:

NOT FOR USE ON ALUMINUM

- 1. Add full contents of package to 2 gallons of water into plastic bucket.
2. Using stirring device, mix the powder in water until completely dissolved.
3. Shut off water supply to the water heater from the inlet and outlet valve and relieve pressure.
4. Disconnect the water heater at the energy source. Disconnect inlet and outlet water valves.
5. Use a recirculation pump to feed the cleaning solution into the water heater. Recirculate for 20 minutes or until the unit is clean. Clean the heat exchanger only. Follow your service manual for specific cleaning instructions.
6. After cleaning, dispose of used cleaning chemicals in accordance with local regulations.
7. With the energy source turned off, flush the water heater thoroughly for 10 minutes with cold water.
8. Reconnect the water heater to the energy source.
9. Reconnect waterheater to the energy source.

READ SDS AND ALL DIRECTIONS FOR USE, HAZARD AND PRECAUTIONARY STATEMENTS ON LABEL BEFORE USING.

Packaging

Table with 5 columns: Code, Size, Qty. per Case, Lbs. per Case, Cubic Feet per Case. Row 1: 68708, 1.2 lbs (544.3 g), 12, 16, .46



Characteristics | Features

- Thorough Cleaning
• Cleans Circulation Coils
• Fast Acting
• Restores Water Flow & Pressure
• Easy to Use
• No Strong Odor
• Biodegradable

Applications

- Any type of tankless water heater.
• Do not use on aluminum.

CALCI-FREE

Tankless Water Heater Flush

Specifications

Color Solid mixture

Shelf Life 2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



Certified to
NSF/ANSI/CAN 60



WARNING!

May be corrosive to metals. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.

CONTAINS: Sulfamic Acid 5329-14-6.

Refer to Safety Data Sheet (SDS) for precautionary statements.

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

3255 Wyandotte St. East • Windsor, ON NBY 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50000-1020