



A CSW Industrials Company

# PRODUCT DATA SHEET

## COIL-RITE™ Evaporator Coil Cleaner

### Description

Non-acid COIL-RITE™ removes grime, oil, grease and dust from air conditioning coils, air handling equipment, as well as electronic and permanent air filters and all mechanical equipment. Powerful surface-active chemicals actually lift grease and dirt off normally inaccessible surfaces. A COIL-RITE cleaning reduces head pressure on over-heated compressors, avoids premature equipment breakdown, increases equipment efficiency and decreases power consumption and costs. It is safe for all metals, including aluminum, when used as directed. No rinsing is required unless surface is painted or wax coated.

### Characteristics | Features

- Cleans grime, oil, grease and dust
- Non-acid, Non- flammable
- Can be used indoors and outdoors
- Will not harm copper or aluminum
- Biodegradable

### Applications

Coil-Rite can be safely used on aluminum, copper, stainless steel and painted surfaces. It is formulated to clean metal coils, fiber or metal mesh filters, and other metal surfaces where acids should not be used.

### Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
82612	Gallon (3.8L)	4	36	1.27

### Instructions

#### READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE

1. Appropriate dilution with water is the key to economic use. For extremely dirty coils and equipment: Dilute with 4 parts of water. For cleaning all types of filters: Dilute with 5 parts of water. For a Continuous Maintenance Program: Dilute with 5 to 10 parts water.
2. Apply the diluted solution with a trigger sprayer, hand powered tank or high pressure washer. Use a brush to help faster penetration of hard encrusted dirt.
3. Allow 5 to 10 minutes soaking time before rinsing. On an operating evaporator coil rinsing is not required since the condensate will flush out all the loosened slime and dirt.

**Special Notes:** On waxed and painted surfaces, COIL-RITE should be rinsed off within a minute of application to avoid the possibility of removing the wax or fading the paint.

## Precautions

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**CAUTION! CAUSES EYE IRRITATION**

### **CONTAINS: Glycol Ether and Surfactant.**

Do not get in eyes, on skin, or on clothing. Wear goggles, and rubber gloves. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. **FIRST AID:** For any overexposure, get immediate medical attention after first aid is given. **EYES** - Flush with large amounts of clean water for at least 15 minutes. **SKIN** - Flush with large amounts of clean water. **Inhalation** - Remove to fresh air. Give Oxygen or artificial respiration if needed. **Ingestion** - Only if conscious, give large amounts of water. If unconscious, do not give anything by mouth or attempt to induce vomiting. **STORAGE AND HANDLING:** Store in cool place away from all food. Keep container upright and tightly closed when not in use. Do not reuse or burn empty container - rinse thoroughly and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet.

## Specifications

Wt/Gal @ 77°F	8.5 ± 0.5 lbs./gal.
Flash Point SETA CC	None
Color	Green
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



Nonfood Compounds  
P1

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by **RectorSeal, LLC · 2601 Spenwick Drive, Houston, TX 77055, USA · 800-231-3345 · Fax 800-441-0051 · [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2019 RectorSeal. All rights reserved. R50128 419