



A CSW Industrials Company

# PRODUCT DATA SHEET

## CTT-EC™ TABLETS Evaporative Cooler Treatment

### Description

CTT-EC Tablets, by placement in the reservoir, automatically provide water treatment proportionate to operating conditions without feeder equipment. They prevent hard water mineral scale, ferrous and non-ferrous corrosion, and silt and soil accumulations in evaporative coolers. Preventing these problems improves efficiencies, reduces break-downs, and decreases power costs.

### Applications

CTT-EC Tablets provide water treatment for evaporative coolers. Tablets are easy to use; just put in and walk away.

### DIRECTIONS FOR USE:

Add one tablet to reservoir for every 3,000 gallons of water evaporated from the system. Add more tablets as needed. For best results, first clean and flush dirty systems.

For additional technical information, call Toll Free 1-800-231-3345.



### Characteristics | Features

- Automatic water treatment
- Improves efficiencies
- Keeps filter clean
- Decreases power costs
- Easy to use
- Reduces break-downs

### Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
68030	4 Tablet Tube - .53 lbs. (240 g)	12	9	0.24

# CTT-EC™ TABLETS

## Evaporative Cooler Treatment

### Specifications

Flash Point SETA CC	None
Color	Blue tablet
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

### Precautionary Statements

Refer to Safety Data Sheet (SDS).

### KEEP OUT OF REACH OF CHILDREN

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

For additional Technical Information Call Toll Free 1-800-231-3345

### Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50754-0121