



# LETSGO™

## PENETRANT, LUBRICANT AND FREEZE-UP PREVENTER

### DESCRIPTION

---

LETSGO™ covers metal surfaces with a clinging, tough, long-lasting film of lubricant. The wetting power acts quickly on badly rusted and seized parts. LETSGO™ penetrates lacquer and paint too. It displaces moisture from wiring and equipment, and continues to protect from water and weather.

### CHARACTERISTICS

---

- \* Quickly loosens frozen bolts, nuts and joints
- \* Protects from water and weather
  
- \* Non-conductive

### APPLICATIONS

---

LETSGO™ may be used to quickly loosen up frozen or seized bolts, nuts and joints. It continues to protect against water and weather damage. It also displaces moisture from wiring .

### PACKAGING

---

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
73012	12 ounce aerosol	12	13	0.52

**INSTRUCTIONS**

---

**READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING**

- SHAKE WELL BEFORE USING
- Spray frozen bolt, nut or joint.

For additional technical information, call Toll Free 1-800-231-3345

**PRECAUTIONS**

---

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**WARNING!  
CONTENTS UNDER PRESSURE. VAPOR HARMFUL  
KEEP OUT OF REACH OF CHILDREN  
READ BACK PANEL CAREFULLY.**

**CONTAINS: ALIPHATIC HYDROCARBONS.** Use only as directed. Store at room temperature. Use with adequate ventilation. Do not spray into fire or on to hot surfaces. Avoid contact with eyes and skin. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120° F.

**FIRST AID: Skin:** Wash off with soap and water. **Eyes:** Flush with plenty of water. Seek medical attention if irritation persists. **Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped, and oxygen if available. Call physician immediately.

For additional information, refer to Material Safety Data Sheet.

**SPECIFICATIONS**

---

Flash Point SETA CC	N/A
Color	Dark grey
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

**LIMITED WARRANTY**

---

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED BY  
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035, USA  
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051  
www.rectorseal.com