

# NEUTRODA™ Powder

FUEL OIL DEODORIZER AND ABSORBENT

## DESCRIPTION

NEUTRODA™ Powder eliminates oil odors and absorbs oil stains from concrete and other floors. Leaves a pleasant odor after absorbing oil from spills and leaks. Sifter top can for controlled economical usage and clean storage.

## CHARACTERISTICS

- \* Absorbs and deodorizes after spills and leaks
- \* Pleasant odor
- \* Non explosive
- \* Non flammable

## APPLICATIONS

NEUTRODA™ Powder is used to deodorize and absorb oil from leaking or overfilled tanks, oil burner drippings, in warm air vents and air filters, in garages, grease pits and on equipment.

## PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68502	1 Lb.	12	16	0.592

# NEUTRODA™ Powder FUEL OIL DEODORIZER AND ABSORBENT

## INSTRUCTIONS

### READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

1. Wipe up excess material from spill or leak.
2. Shake **NEUTRODA™ Powder** lightly on entire area of leak or spill.
3. To assure permanent effect, **NEUTRODA™ Powder** should not be swept up immediately.
4. If oil spill or leak is inaccessible to powder, use **ODORGON™ Spray**.
5. Use **NEUTRODA™ Powder** regularly and avoid repeat calls due to odor complaints.

For additional technical information, call Toll Free 1-800-231-3345

## PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**CAUTION: EYE IRRITANT. KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID: Eyes:** Flush with plenty of water for 15 minutes. **Ingestion:** Induce vomiting if swallowed. Consult physician. **Skin:** Wash with soap and water.

For additional information, refer to Material Safety Data Sheet.

## SPECIFICATIONS

Wt/Gal @ 77°F	Solid
Flash Point SETA CC	None
Color	Off White to Yellow
Shelf Life	2 Years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY  
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035  
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051  
www.rectorseal.com