



SAFETY DATA SHEET

NOKORODE® REGULAR
Soldering paste flux

SECTION 1 – PRODUCT AND COMPANY INFORMATION

Product Name
Nokorode® Regular Paste Flux

Product Codes
14000, 14003, 14010, 14020, 14030

Chemical Family
Organic/Inorganic

Use
Soldering flux

Manufacturer's Name
The RectorSeal Corporation
2601 Spenwick Drive
Houston, Texas 77055 USA

Date of Validation
January 23, 2015

Date of Preparation
May 2, 2012

HMIS Codes

Health	1
Flammability	1
Reactivity	0
PPI	B

Emergency Telephone No.
Chemtrec 24 Hours
(800)-424-9300 USA
(703)-527-3887 International

Technical Service Telephone No.
(800)-231-3345 or (713)-263-8001

SECTION 2 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

OSHA Hazards

Irritant

GHS CLASSIFICATION

Physical Hazards

None

Health Hazards

Acute Toxicity:

- Oral: Not Classified
- Dermal: Not Classified
- Inhalation: Not Classified
- Skin Corrosion/Irritation: Not Classified
- Serious Eye Damage/Eye Irritation: Not Classified
- Respiratory or Skin Sensitization: Not Classified

Germ Cell Mutagenicity: Not Classified
Carcinogenicity: Not Classified
Reproductive Toxicology: Not Classified
Target Organ Systemic Toxicity - Single Exposure: Not Classified
Target Organ Systemic Toxicity - Repeated Exposure: Not Classified

Aspiration Toxicity: Not Classified

ENVIRONMENTAL HAZARDS

Hazardous to the Aquatic Environment: Not Classified
Acute aquatic toxicity: Not Classified
Chronic aquatic toxicity: Not Classified
Bioaccumulation potential: Not Classified
Rapid degradability: Not Classified

GHS Label elements, including precautionary statements



GHS07: Exclamation Mark/Irritant

Signal Word: **Warning**

Hazard Statements:

H302 - Harmful if swallowed.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.

Precautionary Statements:

P102 - Keep out of reach of children.
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash hands thoroughly after handling.
P281 Use personal protective equipment as required.

Summary Of Acute Hazards

Irritation to respiratory system from fumes evolved during soldering. Eye contact may cause intense irritation and injury.

Route Of Exposure, Signs And Symptoms

INHALATION

Irritation to respiratory system from fumes evolved during soldering.

EYE CONTACT

Contact may cause intense irritation and injury.

SKIN CONTACT

May cause skin irritation.

INGESTION

Nausea, vomiting, irritation to digestive system.

SUMMARY OF CHRONIC HAZARDS

Short term effects to liver and kidneys can occur. Chemical irritation from continued skin contact can occur. Continuous industrial use in small unventilated areas may result in sufficient inhalation of solder and flux fumes to cause lung damage and irritation of respiratory tract.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient: Zinc Chloride

Percentage By Weight: 10-25

CAS Number: 7646-85-7

EC#: 231-592-0

Ingredient: Ammonium Chloride

Percentage By Weight: 10-25

CAS#: 12125-02-9

EC#: 235-186-4

Ingredient: Petrolatum

Percentage By Weight: 70-90

CAS#: 8009-03-8

EC#: 232-373-2

SECTION 4 – FIRST AID MEASURES

- If inhaled: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
- If on skin: Immediately wash with soap and water. Remove and wash any contaminated clothing.
- If in eyes: Immediately flush with large amounts of water for at least 15 minutes. Get medical attention if irritation persists.
- If swallowed: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media

Foam, dry chemical, carbon dioxide or water fog.

Special Fire Fighting Procedures: Wear self-contained full face piece breathing apparatus and other protective clothing. Hazardous decomposition products possible (see Section 10). May release ZnO and HCl fumes.

Unusual Fire And Explosion Hazards: Heat may build up pressure and rupture closed containers.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Wipe up spills to prevent footing hazard. Avoid flushing into sewers, drains, waterways and soil. Wear protective clothing during clean up.

SECTION 7 – HANDLING AND STORAGE

Precautions To Be Taken In Handling And Storing: Keep container closed and upright when not in use. Store flux at ambient conditions. Wash thoroughly after handling to remove all residue.

Other Precautions: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredient	Units
------------	-------

Zinc Chloride

ACGIH TLV:	1 mg/m ³
------------	---------------------

OSHA PEL:	1 mg/m ³
-----------	---------------------

Ammonium Chloride

ACGIH TLV:	10 mg/m ³
------------	----------------------

OSHA PEL:	10 mg/m ³
-----------	----------------------

Petrolatum

ACGIH TLV:	N/D
------------	-----

OSHA PEL:	N/D
-----------	-----

Respiratory Protection (Specify Type): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators during soldering operations until fumes have dissipated.

Ventilation – Local Exhaust: Acceptable

Special: N/A

Mechanical (General): Acceptable.

Other: N/A

Protective Gloves: Wear rubber gloves.

Eye Protection: Safety glasses (ANSI Z-87.1 or equivalent)

Other Protective Clothing Or Equipment: Coveralls recommended.

Work/Hygienic Practices: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling point:	N/A
Specific gravity (H ₂ O = 1):	1.06
Vapor pressure (mmHg):	< 0.01 @ 68°F (20°C)
Melting point:	120° – 150°F (52° – 66°C)
Vapor Density (Air = 1):	N/A
Evaporation rate (Ethyl Acetate = 1):	N/A
Appearance/Odor:	Tan/Petroleum odor
Solubility in water:	Insoluble
Volatile Organic Compounds (VOC) Content (theoretical percentage by weight):	0% or (0 g/L)
Flash point:	> 400°F (204°C) SETA CC
Lower explosion limit:	N/D
Upper explosion limit:	N/D

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions To Avoid: None

Incompatibility (Materials To Avoid): None known

Hazardous Decomposition Products: Toxic fumes of zinc, chlorine, and HCL may be evolved during soldering.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGY INFORMATION

Chronic Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Toxicology Data

Ingredient Name

Zinc Chloride

Oral-Rat LD50:	350 mg/kg
Inhalation-Rat LCLo:	1960 mg/m ³ /10M

Ammonium Chloride

Oral-Rat LD50: 1650 mg/kg
 Inhalation-Rat LC50: N/D

Petrolatum

Oral-Rat LD50: N/D
 Inhalation-Rat LC50: N/D

SECTION 12 – ECOLOGICAL INFORMATION

Ecological Data

Ingredient Name: **Zinc Chloride**
 Food Chain Concentration Potential: None
 Waterfowl Toxicity: N/A
 BOD: None
 Aquatic Toxicity: 7.2 ppm/96 hr/medium bluegill/TLm

Ingredient Name: **Ammonium Chloride**
 Food Chain Concentration Potential: None
 Waterfowl Toxicity: N/A
 BOD: N/A
 Aquatic Toxicity: 6 ppm/96 hr/sunfish TLm

Ingredient Name: **Petrolatum**
 Food Chain Concentration Potential: N/D
 Waterfowl Toxicity: N/D
 BOD: N/D
 Aquatic Toxicity: N/D

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in accordance with federal, state, and local regulation regarding pollution.

SECTION 14 – TRANSPORTATION INFORMATION

DOT:	Non-regulated
Ocean (IMDG):	Non-regulated
Air (IATA):	Non-regulated
WHMIS (Canada):	Non-regulated

SECTION 15 – REGULATORY INFORMATION

Regulatory Data

Ingredient Name:	Zinc Chloride
SARA 313	Yes
TSCA Inventory	Yes
CERCLA RQ	1,000 lb.
RCRA Code	N/A

Ingredient Name:	Ammonium Chloride
SARA 313	No
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

Ingredient Name:	Petrolatum
SARA 313	No
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

SECTION 16 – OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made.

Consult RectorSeal for further information: (713) 263-8001