



A CSW Industrials Company

PRODUCT DATA SHEET

RENEWZ™

Foaming Coil Cleaner & Brightener for Condenser

Description

Renewz is a non-acid foaming brightener and cleaner for finned, air-cooled condenser coils. Renewz penetrating, surfactant aided, foaming action lifts and pushes contaminants and oxides off the coils, including difficult to remove cooking greases found coating coils in restaurants, and tobacco stains on air filters. Renewz is biodegradable. Can be use for cleaning electronic air filters

Instructions

- Dilute RENEWZ with cold water only (below 100°F)
 - Brightening, Oxides, Heavy dirt & grease removal Dilute 1 part Renewz to 3 parts water
 - Some brightening, Light to medium dirt & grease removal Dilute 1 part Renewz to 6 parts water
 - No brightening, Light dirt removal..... Dilute 1 part Renewz to 9 parts water
- Shut off system.
- Spray the diluted RENEWZ on to all surfaces, saturating the coils well. Use a low pressure sprayer that does not contain aluminum. Do not use high pressure washers. Avoid backspray from wind.
- Allow 5 minutes for full cleaning action, but never more than 8 minutes.
- Rinse coils and surrounding area very thoroughly with low pressure water.
- For cooking grease applications, allow 8 minutes before rinsing. Repeat if necessary.

Applications

Renewz may be safely used on aluminum, copper or stainless steel and will not cause damage if used as directed.

For industrial use only by trained professional personnel.



Characteristics | Features

- Commercial strength
- Non-acid, Non-flammable
- Biodegradable
- Foaming action penetrates stubborn grease, tars and dirt, solubilizes and disperses them so they can be rinsed away with water
- Concentrated - dilute with water for economical use
- Leaves aluminum surfaces not only bright and shiny, but completely clean and free of particulate matter in less than five minutes.
- Will not harm copper or aluminum
- Contains corrosion inhibitor

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
82644	Gallon (3.8 L)	4 Bottles	45	1.21
82646	5 Gallons (18.9 L)	1 Pail	55	1.10
82650	55 Gallons (208 L)	1 Drum	612	9.01

Specifications

Wt./Gal @ 77°F	10.0 lbs./gal.
Flash Point SETA CC	None
Color	Blue
Shelf Life	2 years



Nonfood Compounds
P1

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

**DANGER!**

Causes severe skin burns and eye damage. May cause respiratory irritation. May be corrosive to metals. **EMITS IRRITATING FUMES** which can accumulate in occupied spaces. DO NOT mix with any acidic product. Keep reacted foam away from open flames.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.

CONTAINS: Sodium Hydroxide 1310-73-2. Causes serious eye damage. Harmful to aquatic life. Keep only in original container. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant stainless steel container with a resistant inner liner. Dispose of contents/container to an approved waste disposal plant. Triple rinse container (or equivalent) promptly after emptying. **KEEP OUT OF REACH OF CHILDREN.**

FOR PROFESSIONAL USE ONLY. USE ON CONDENSER COILS ONLY. DO NOT USE ON EVAPORATOR OR HEAT EXCHANGE COILS.

For additional information, refer to Safety Data Sheet.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2019 RectorSeal. All rights reserved. R50127-0919