



A CSW Industrials Company

PRODUCT DATA SHEET

SAM™ CL-3L

Low VOC Cleaner for PVC, CPVC and ABS

Description

Sam CL-3L is a clear cleaner for use on all PVC, CPVC and ABS pipe, tubing, and socket-type fittings. Max VOC per SCAQMD 1171: 25 g/L.

Instructions

1. Store between 40°F and 110°F and apply between -15°F and 120°F. Use below 40° F only with proper solvent cement and with extreme care. Use this cleaner to remove grease, oil, and dirt from bonding surfaces of PVC, CPVC and ABS pipe and fittings. Wear non-permeable gloves during application to avoid skin contact.
2. Clean fitting socket and pipe, and check for proper fit.
3. Using supplied dauber applicator, apply CLEANER evenly and freely to socket and then to pipe end for length of socket depth. Then apply again to socket. Avoid puddling. For pipe greater than 2" diameter use natural-bristle brush sized to 1/2 of the pipe diameter.
4. Temperature and humidity conditions may require repeated applications to one or both surfaces to avoid drying. While still wet, quickly apply proper solvent cement and make up pipe joint in accordance with the solvent cement's instructions.

For additional technical information, call Toll Free 1-800-231-3345.

Applications

Sam CL-3L is specifically formulated as a cleaner for use on all PVC, CPVC, and ABS pipe applications such as potable water, pressure pipe, conduit, sewers and drain, waste and vent (DWV). It is for use with all sizes and classes in both Schedule 40 and Schedule 80.



Characteristics | Features

- Safe for use on potable water systems
- Helps make a clean, professional looking joint
- Acts as a cleaner by dissolving grease and dirt and helping prepare the bonding surfaces for solvent cementing
- Good for PVC, CPVC and ABS systems

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
55929	1/4 Pint Dauber top (118 ml)	24 Cans	10	.18
55930	1/2 Pint Dauber top (237 ml)	24 Cans	16	.45
55932	Pint Dauber top (473 ml)	12 Cans	15	.43
55934	Quart Dauber top (946 ml)	12 Cans	28	.78

Specifications

Wt/Gal @ 77°F	6.5 lbs./gal.
Flash Point SETA CC	-20°C (-4°F) TCC based on Acetone
Color	Clear
Shelf Life	3 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



DANGER!

Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet (SDS).

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50099-0921