



SEALMASTER™

BOILER LEAK SEALER

DESCRIPTION

SEALMASTER™ fills and seals cracks, holes and loose joints in steam systems. It forms a cement-like water-tight plug. SEALMASTER™'s unique corrosion inhibitor protects the boiler's surface from pitting, even after complete draining.

CHARACTERISTICS

- * Seals leaks
- * Inhibits corrosion in steam boilers
- * Contains no petroleum distillates
- * Will not harm seals or gaskets

APPLICATIONS

SEALMASTER™ is used to seal leaks in Steam boilers, hot water boilers and baseboard radiators. SEALMASTER™ should be used on new installations and whenever piping repairs, related to the steam and hydronic systems, are made. This procedure will help assure the elimination of costly and annoying leaks.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68722	Quart	12	30	0.71
68724	Gallon	6	71	1.25

SEALMASTER™ BOILER LEAK SEALER

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

IN STEAM BOILERS:

- Fill boiler to water line in order to seal all leaks below water level.
- Use one quart of SEALMASTER™ for each 600 sq. ft. of steam radiation, 150 MBH, 1.5 GPH or 4.4 hp nozzle rating.
- Heat water to boiling.
- After leak has stopped, completely drain boiler. The removal of chemical solids helps prevent surging in steam boilers.

HOT WATER BOILERS:

- Add 1 quart of SEALMASTER™ to every 50 gals. of water.
- Turn off recirculating pump and heat boiler for approximately one hour.
- Drain boiler, refill, and turn recirculating pump on.

Shake well before using !

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

WARNING!

SKIN AND EYE IRRITANT.

KEEP OUT OF REACH OF CHILDREN.

CONTAINS: SODIUM SILICATE. Avoid contact with eyes and skin. Wash thoroughly after handling. **FIRST AID: Skin:** Wash with soap and water. **Eyes:** Flush with water for 15 minutes. If irritation persists, seek medical aid. **Ingestion:** If swallowed, DO NOT induce vomiting. Give victim a glass of water. Call a physician immediately. Never give anything by mouth to an unconscious person.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	11.85 lbs/ gal
Flash Point SETA CC	None
Color	White liquid
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY

RectorSeal® • 2601 Spenwick Drive • Houston, Texas 77055-1035

Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051

www.rectorseal.com