



A CSW Industrials Company

PRODUCT DATA SHEET

SEALMASTER™ Boiler leak sealer

Description

Sealmaster fills and seals cracks, holes and loose joints in steam systems. It forms a cement-like water-tight plug. Sealmaster's unique corrosion inhibitor protects the boiler's surface from pitting even after complete draining.

Applications

Sealmaster is used to seal leaks in steam boilers, hot water boilers, and baseboard radiators. Sealmaster should be used on new installations and during piping repairs, related to the steam and hydronic systems are made. This procedure will help assure the elimination of costly and annoying leaks.

Directions for Use

READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

(shake well before using)

Steam Boiler (1) Fill boiler to water line. (2) Add 1 qt. of Sealmaster to each 600 sq. ft. of steam radiation, 150MBH or 1.5 GPH nozzle rating. (3) Heat water to boiling. (4) When leak has stopped, completely drain boiler to flush chemical residue. (5) Refill boiler and restart system.

Hot Water Boiler (1) Add 1 qt. of Sealmaster to each 50 gallons of water. (2) Turn off recirculating pump and boiler for 1 hour. (3) Completely drain boiler to flush chemical residue. (4) Refill boiler and restart recirculating pump and boiler.

For large leaks pack with steel or lead wool. A second treatment may be necessary. To avoid damaging recirculating pump, if more than 2 treatments are needed, consult with boiler manufacturer.

Note: Contains no petroleum distillates - safe for systems.

For additional technical information, call Toll Free 1-800-231-3345

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
68722	Quart (.946 l)	12	31	0.71



Characteristics | Features

- Fill holes & loose joints
- Corrosion inhibiting protective coating
- No petroleum distillates
- Will not harm seals or gaskets

Specifications

Wt/Gal @ 77°F	11.85 lbs/gal
Flash Point SETA CC	None
Color	White liquid
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances



WARNING! Causes serious eye irritation. Causes skin irritation. Harmful if swallowed.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300.

Contains: Sodium Silicate 1344-09-8, Bentonite 1302-78-9, Wollastonite 13983-17-00, Gum Rosin 8050-09-7, Water 7732-18-5.

Precautionary Statements - PREVENTION: Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. **RESPONSE: IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF ON SKIN (or hair):** Wash with plenty of water. **If skin irritation occurs:** Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF SWALLOWED:** Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Safety Data Sheet, or Call Toll Free 1-800-231-3345.

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50490-0720