

STEAMASTER™ TABLETS

CONCENTRATED BOILER TREATMENT

DESCRIPTION

STEAMASTER™ TABLETS remove and prevent scale and corrosion in steam and hot water systems.
STEAMASTER™ TABLETS provide measured doses – no mixing, no measuring and no waste.

CHARACTERISTICS

- * Removes and prevents corrosion and scale.
- * Color coded for accurate dosage
- * Contains no petroleum distillates
- * Will not harm rubber or synthetic seals or gaskets
- * Easy to use tablets

APPLICATIONS

STEAMASTER™ TABLETS are used in steam and hot water systems to remove and prevent scale and corrosion. Easy to use tablets take the guesswork out of dosage quantity. Just place in any convenient opening in system.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68732	36 Tablet Tub	12	13	0.56

STEAMASTER™ TABLETS CONCENTRATED BOILER TREATMENT

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

FOR CLEANING VERY DIRTY STEAM BOILERS WITH EXCESSIVE SCALE, RUST AND SLIME:

- 6 tablets for each 100 sq. ft. of radiation, 25 MBH or .25 GPH nozzle rating, or until water turns violet.
- Drop tablets into any convenient opening. Allow to steam for ½ to 3 hours, then drain and flush.
- Refill boiler and add 4 tablets for each 100 sq. ft. of radiation to act as a rust inhibitor and conditioner. LEAVE THEM IN.

FOR MAINTAINING CLEAN, RUSTFREE WATER AND FOR NEW INSTALLATION:

- 4 tablets for each 100 sq. ft. of radiation, 25 MBH or .25 GPH nozzle rating, or until water turns violet.
- Drop them in. LEAVE IN. Conditions water for full season.

FOR HOT WATER SYSTEMS:

- Use 4 tablets for each 5 gallons of circulating water or until water turns violet.
- Stops corrosion and stagnant odors.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

DANGER  POISON!

MAY BE FATAL IF SWALLOWED
IRRITATING TO EYES AND SKIN

CONTAINS SODIUM NITRITE. KEEP OUT OF REACH OF CHILDREN.

FIRST AID: **Skin:** Avoid prolonged contact with skin. If exposed, wash promptly and thoroughly with soap and water. **Eyes:** If the product gets into the eyes, flood eyes immediately and thoroughly with clean, cool water. If irritation persists, consult a physician. **Ingestion:** If swallowed, call a physician at once. Give victim a glass of water and INDUCE vomiting. Never give anything by mouth to an unconscious person.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	Solid
Flash Point SETA CC	None
Color	Tablets with blue dots
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com