



## SOOTOMAGIC™

### THROW-IN SOOT REMOVER

#### DESCRIPTION

---

SOOTOMAGIC™ is the original soot stick. SOOTOMAGIC™ destroys soot by high temperature ignition, catalytic low temperature ignition and a residual soot removal coating that works even after the stick is consumed.

#### CHARACTERISTICS

---

- \* Removes insulating soot
- \* Non-corrosive
- \* Fits through all combustion chamber openings.
- \* Contains no lead
- \* Non-explosive

#### APPLICATIONS

---

SOOTOMAGIC™ is used to remove insulating soot from oil burners. Place stick through combustion chamber port. One SOOTOMAGIC™ stick is good for up to 400 sq. ft. of radiation.

#### PACKAGING

---

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68332	¼ lb. Stick	48	14	0.36

# SOOTOMAGIC™ THROW-IN SOOT REMOVER

## INSTRUCTIONS

---

### READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

One SOOTOMAGIC™ stick is good for up to 2.4 hp or 400 sq ft heating surface.

1. Run burner until chamber is hot.
2. Throw unopened pack through peephole.
3. Keep inspection doors and ports closed.

For additional technical information, call Toll Free 1-800-231-3345

## PRECAUTIONS

---

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**PRECAUTIONS:** Harmful if swallowed. Wash hands after handling.  
**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:** For any overexposure get immediate medical attention after first aid is administered.

**Skin:** Wash with soap and water. **Eyes:** Flush with clean water for 15 minutes.

**Ingestion:** Call physician.

For additional information, refer to Material Safety Data Sheet.

## SPECIFICATIONS

---

Wt/Gal @ 77°F	Solid
Flash Point SETA CC	None
Color	Dark Powder
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

## LIMITED WARRANTY

---

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED BY

Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055

Telephone: 713/263-8001 or 800/231-3345 Fax: 713/263-7577 or 800/441-0051

[www.rectorseal.com](http://www.rectorseal.com)