



NICKEL-SAFE ICE MACHINE CLEANER

FOOD GRADE ACID CLEANER

DESCRIPTION

Nickel-Safe Ice Machine Cleaner is formulated to be the safest product for nickel-plated evaporators. It assures clean cold taste-free ice by stripping ice machines of scale, muck & slime. In cube or flake ice, these impurities can cause opacity, bad taste and foul odors.

CHARACTERISTICS

- * Food grade acid cleaner
- * Safe for nickel plated surfaces
- * Removes scale, muck and slime
- * Opens constricted water lines
- * Meets Manitowoc Spec. GES-6

APPLICATIONS

Nickel-Safe Ice Machine Cleaner strips away scale, sludge and muck from ice forming surfaces and water lines. This specially formulated product removes impurities that cause cloudy, bad tasting and foul smelling ice.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
88312	16 Oz.	12	17	0.52
88314	Gallon	4	41	1.27

NICKEL-SAFE ICE MACHINE CLEANER FOOD GRADE ACID CLEANER

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

- 1) Wear safety goggles and rubber or plastic gloves.
- 2) Cut off refrigeration and water supply and bleed lines. Remove all ice from the machine.
- 3) Remove water trough, curtain, distribution tube and other parts which are contacted by water.
- 4) Mix 3 ounces of **Nickel-Safe Ice Machine cleaner** per gallon of warm water. Place machine parts into the solution and soak. Loosen the scale with a soft brush, if necessary.
- 5) Clean the storage bin and cabinet with a sponge or rag soaked with the solution. Rinse thoroughly with fresh water.
- 6) Rinse the soaked parts with fresh water and replace them. Turn on water.
- 7) Add 5 ounces of **Nickel-Safe Ice Machine Cleaner** per gallon of water in the machine and circulate for at least 10 minutes, or until all scale is gone. Be sure that all drains are clear.
- 8) Drain all recirculating solution and flush with fresh water for at least 1 minute until all color is gone. Replace the drain plug.
- 9) To assure the highest quality ice, thoroughly rinse the bin with fresh water.
- 10) Restart the machine and discard the first batch of ice.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300
DANGER! CORROSIVE.**

**CAUSES SEVERE IRRITATION AND BURNS TO EVERY AREA OF CONTACT.
HARMFUL IF SWALLOWED OR INHALED**

CONTAINS PHOSPHORIC ACID. Vapors irritating to eyes and respiratory tract. Avoid all direct contact and breathing fumes. Use only with rubber gloves and splashproof goggles in a well ventilated area. **KEEP OUT OF REACH OF CHILDREN. FIRST AID: SKIN:** Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician immediately. Wash clothing before reuse. **EYES:** Immediately flush eyes with gentle but large stream of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Call a physician immediately. **INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	10.6 lbs/gal
Flash Point SETA CC	None
Color	Dark Green
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055
Telephone: 713/263-8001 or 800/231-3345 Fax: 713/263-7577 or 800/441-0051
www.rectorseal.com A-02