



A CSW Industrials Company

## PRODUCT DATA SHEET

# GULFCLEAN™ Salt Reducer

### Description

For long-term coating protection, RectorSeal® GulfClean™ Salt Reducer dissolves soluble salts and revitalizes HVAC equipment. By removing soluble salts, the service life of the equipment and coatings may be extended. Will not interfere with the adhesion of protective coatings.

### Directions

Ensure coils are thoroughly cleaned first with GulfClean Coil Cleaner.

1. If frozen, thaw and shake before use.
2. For condenser coils, shut off system before cleaning. For evaporator coils, system may remain on. In confined areas, shut off any ignition sources and provide adequate ventilation.
3. Using a pump up sprayer, fill to the appropriate level with potable water and add GulfClean Salt Reducer. Leave room for pump plunger to be reinserted. Inland applications have 100:1 ratio; Coastal applications have 50:1 ratio.
4. Wear protective gear. Apply to all external coil surfaces with a steady pressure. Start at top and work side to side toward bottom to thoroughly saturate coil. Keep wet.
5. Soak coils by spraying directly on and into the fin pack section. Let stand for 5 to 10 minutes, DO NOT let dry before rinsing.
6. Using pressurized (not to exceed 100psi) potable water rinse the GulfClean Salt Reducer and dissolved salts off of coils starting at the top of the coil and moving side to side until you reach the bottom. Repeat as many times as necessary to thoroughly rinse the coils.
7. Reinstall all panels and let dry.

NOTE: Every 6 months coils are cleaned using approved 2 step method products, for long term coating protection and to maintain Modine® ElectroFin® E-Coat and Insitu® Spray coating warranty.



### Applications

- Evaporator Coils
- Condenser Coils

### Characteristics | Features

- No VOC's
- Non-flammable
- Aids in the removal of soluble salts
- Does not interfere with the adhesion of protective coatings

### Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
80408	1 Gallon (3.76 Liters)	4	38	1.21

## Specifications

Wt/Gal @ 77°F	8.7 lbs./gal.
Flash Point	SETA CC None
Color	Blue
Odor	Irritating Odor
Shelf Life	3 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



## Precautionary Statements

Refer to Safety Data Sheet (SDS).

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.**

**KEEP OUT OF REACH OF CHILDREN.**

For additional information, Call Toll Free 1-800-231-3345.

 **WARNING:** This product can expose you to chemicals including N, N-Diethanolamine and Ethylene glycol, which is known to the State of California to cause cancer, birth defects or reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal, LLC**

**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

**PO Box 3119 DC • Clontarf QLD 4019, Australia • 073267 7277 • [rectorseal.com.au](http://rectorseal.com.au)**

**3255 Wyandotte St. East • Windsor, ON N8Y 1E9, Canada • 519-966-4901**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50365-0721