

Andersons Golf Products

Turf Fertilizer

21-0-20

with Poly-S® Nitrogen

- Contains Poly-S Nitrogen
- Contains Potassium Sulfate

Guaranteed Analysis	
Total Nitrogen (N)	21.00%
21.00% Urea Nitrogen*	
Soluble Potash (K ₂ O)	20.00%
Sulfur (S)	8.75%
1.95% Free Sulfur (S)	
6.80% Combined Sulfur (S)	
Derived from potassium sulfate and polymer coated sulfur coated urea.	
*21.00% Slowly available urea nitrogen from polymer coated sulfur coated urea.	
F002091	
Information regarding the contents and levels of metals in this product is available on the internet at http://www.aapfco.org/metals.html	

FLORIDA APPLICATIONS:

We recommend that you follow the Florida Green Industries BMP's at:

<http://www.flrules.org/Gateway/reference.asp?No=Ref-04706>

We recommend that you follow the Florida Golf Course BMP's at:

<http://www.flrules.org/Gateway/reference.asp?No=Ref-04702>

Nitrogen Notice: For those states with nitrogen application restrictions, including but not limited to MD, NH, NH and VA, do not apply more than 3.6 lbs. of this product per 1,000 sq. ft.

DIRECTIONS FOR USE

Apply only as directed during the growing season. Apply when a regular feeding of nitrogen and potassium along with sulfur is desired.

Application Rates:

LOW: 3.6 lbs/1000 sq. ft.

MEDIUM: 4.8 lbs/1000 sq. ft.

- For All Applications:**
- Apply to dry foliage.
 - Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
 - Do not collect clippings for at least one mowing following application to avoid particle pick-up.

- Cool Season Grasses:**
- Apply at the LOW OR MEDIUM RATE.
 - Exception: Apply at the LOW RATE when temperatures exceed 85°F.

- Warm season grasses:**
- Apply at the LOW OR MEDIUM RATE.
 - Exception: Apply at the LOW RATE when temperatures exceed 90°F.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to turf and sweep any product that lands on the driveway, sidewalk or street, back onto the turf.

STORAGE AND USE

Store in a clean, dry place.

Reseal opened bag by folding top down and securing.

Use only clean, dry spreaders.

Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

Poly-S is a registered trademark of The Scotts Company.

Suggested Spreader Settings				
These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.				
50 lbs. feeds 13,800 sq. ft. (0.32 acre) with 0.75 lbs. N/1,000 sq. ft. at the LOW RATE				
50 lbs. feeds 10,400 sq. ft. (0.24 acre) with 1.00 lbs. N/1,000 sq. ft. at the MEDIUM RATE				
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS	
			LOW RATE 3.6 lbs/1,000 sq. ft.	MEDIUM RATE 4.8 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 6); Andersons 2000 SR / SR-2000 (cone 6)	3 mph	10 feet	L 1/2	M 1/2
Scotts R-8, R-8A (cone 6)	3 mph	10 feet	K	L 1/2
Lesco 020093 (pattern 0.25)	3 mph	9 feet	E	F
Lesco 705698 (pattern 0.25)	3 mph	9 feet	13	14
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern I	4.5 mph	36 feet	4 3/4	6 1/2
Vicon 03 Series	4.5 mph	28 feet	21	26

SGN 150

Net Wt. 50 Lbs. (22.68 kg)



10004895 (AGC8391.40)