Andersons Golf Products

Fertilizer

with NS-54™ Nitrogen

- Contains controlled release nitrogen for extended feeding
- Provides initial green-up along with minimal surge growth

Guaranteed Analysis

Total Nitrogen (N)	43.00%
43.00% Urea Nitrogen*	
Sulfur (S)	4.00%
4.00% Free Sulfur (S)	

Derived from polymer coated sulfur coated urea.

*43.00% Slowly available urea nitrogen from polymer coated sulfur coated urea.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at http://www.aapfco.org/metals.html

DIRECTIONS FOR USE

Apply only as directed. Use this product on actively growing fairways and roughs whenever a high nitrogen feeding with quick green-up and controlled-release nitrogen are desired.

Application Rates:

LIGHT: 2.3 lbs/1,000 sq. ft. LOW: 2.9 lbs/1,000 sq. ft. MEDIUM: 3.5 lbs/1.000 sq. ft. HIGH: 4.1 lbs/1.000 sq. ft.

FLORIDA APPLICATIONS:

We recommend that you follow the Florida Green Industries BMP's at: http://www.flrules.org/Gateway/reference.asp?No=Ref-04706

We recommend that you follow the Florida Golf Course BMP's at: http://www.flrules.org/Gateway/reference.asp?No=Ref-04702

For all applications:

- For use on fairways and roughs.
- DO NOT USE ON GREENS OR OTHER LOW-CUT TURF.
- · Do not apply with a drop-type spreader.
- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- For cool season grasses, apply at the LIGHT RATE in mid-summer when temperatures are above 80°F .
- For warm season grasses, apply at LIGHT RATE during mid-summer when temperatures are extreme (90°F or above).

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

Storage and use:

Store in a clean, dry place. Reseal opened bag by folding top down and securing. Use only clean, dry spreaders. Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS: YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by: The Andersons, Inc. P.O. Box 119 Maumee, OH 43537 www.andersonsplantnutrient.com

NS-54 is a trademark of The Andersons, Inc.

Suggested Spreader Settings

Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader before applying product.

50 lbs. feeds 21,700 sq. ft. (0.50 acres) with 0.99 lbs. N/1,000 sq. ft. at the LIGHT RATE

50 lbs. feeds 17,200 sq. ft. (0.39 acre) with 1.25 lbs. N/1,000 sq. ft. at the LOW RATE

50 lbs. feeds 14,200 sq. ft. (0.33 acre) with 1.50 lbs. N/1,000 sq. ft. at the MEDIUM RATE

50 lbs. feeds 12,100 sq. ft. (0.28 acre) with 1.76 lbs. N/1,000 sq. ft. at the HIGH RATE

			SPREADER SETTINGS					
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LIGHT RATE 2.3 lbs/1,000 sq. ft.	LOW RATE 2.9 lbs/1,000 sq. ft.	MEDIUM RATE 3.5 lbs/1,000 sq. ft.	HIGH RATE 4.1 lbs/1,000 sq. ft.		
Andersons Model 2000 / AccuPro 2000 (cone 2); Andersons 2000 SR / SR-2000 (cone 2)	3 mph	10 feet	J 3/4	K 1/4	L	L 1/2		
Scotts R-8, R-8A (cone 2)	3 mph	10 feet	I 1/2	J	J 1/2	К		
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-A	4.5 mph	28 feet	4 1/4	4 1/2	4 3/4	5		
Vicon (03 Series)	4.5 mph	26 feet	25	28	30	33		

SGN 240 Net Wt. 50 Lbs. (22.68 kg)



10003156 (AGC4315.40)