# **Andersons Golf Products**

Turf Fertilizer 23-0-6



- Contains iron for improved turf color
- Fortify–N features dual nitrogen stabilizer technology minimizing risk from environmental losses such as volatilization, leaching and denitrification.

## **Guaranteed Analysis**

| Total Nitrogen (N)                                      | 23.00% |
|---|--------|
| 23.00% Urea Nitrogen*                                   |        |
| Soluble Potash (K <sub>2</sub> 0)                       | 6.00%  |
| Iron (Fe)   | 2.00%  |
|   |        |
| Derived from urea, potassium chloride and ferric oxide. |        |
| Chlorine (CI) Max                                       | 5.08%  |

\*11.50% nitrogen stabilized with N-(n-butyl) thiophosphoric triamide, and dicyandiamide

F002091

Information regarding the contents and levels of metals in this product is available on the internet at http://www.aapfco.org/metals.html

## **DIRECTIONS FOR USE**

Apply only as directed. Apply during the growing season.

### **Application Rates:**

LIGHT: 2.17 lbs/1,000 sq. ft.

LOW: 3.26 lbs/1,000 sq. ft.

MEDIUM: 4.35 lbs/1,000 sq. ft. HIGH: 5.44 lbs/1,000 sq. ft.

#### For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

## **Cool Season Grasses:**

- Apply at the LOW or MEDIUM RATE.
- Apply at the LIGHT RATE when temperatures exceed 85°F.

#### Warm Season Grasses:

Apply at the LOW to HIGH RATE every 4-6 weeks during the period of active growth.

Nitrogen Notice: For those states with nitrogen application restrictions, including but not limited to, MD, NH, NJ and VA, do not apply more than 3.26 lbs of this product per 1,000 sq. ft.

**Note:** This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

## STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

#### **IMPORTANT: READ BEFORE USE:**

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

#### WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

#### **LEGAL RIGHTS:**

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION.

Product of U.S.A.

Manufactured by: **The Andersons, Inc.** P.O. Box 119 Maumee, OH 43537 www.andersonsplantnutrient.com

Fortify is a registered trademark of The Andersons, Inc.

## Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.
Please calibrate your spreader before applying product.
50 lbs. feeds 23,000 sq. ft. (0.53 acre) with 0.50 lbs. N/1,000 sq. ft. at the LIGHT RATE
50 lbs. feeds 15,300 sq. ft. (0.25 acre) with 0.75 lbs. N/1,000 sq. ft. at the LOW RATE
50 lbs. feeds 11,400 sq. ft. (0.26 acre) with 1.00 lbs. N/1,000 sq. ft. at the HEDIUM RATE
50 lbs. feeds 9,100 sq. ft. (0.21 acre) with 1.25 lbs. N/1,000 sq. ft. at the HIGH RATE

| SPREADER  |                 | WIDTH OF<br>COVERAGE | SPREADER SETTINGS                    |                                    |                                       |                                     |
|---|-----------------|----------------------|--------------------------------------|------------------------------------|---------------------------------------|-------------------------------------|
|   | GROUND<br>SPEED |                      | LIGHT RATE<br>2.17 lbs/1,000 sq. ft. | LOW RATE<br>3.26 lbs/1,000 sq. ft. | MEDIUM RATE<br>4.35 lbs/1,000 sq. ft. | HIGH RATE<br>5.44 lbs/1,000 sq. ft. |
| Andersons Model 2000 / AccuPro 2000 (cone 6);<br>Andersons 2000 SR / SR-2000 (cone 6) | 3 mph           | 11 feet              | J 3/4                                | K 3/4                              | M 1/2                                 | N 1/4                               |
| Scotts R-8, R-8A (cone 6)   | 3 mph           | 11 feet              | I 1/4                                | J 3/4                              | K 1/2                                 | M 1/4                               |
| Lesco 020093 (pattern 0.25)   | 3 mph           | 7 feet               | D 1/2                                | D 3/4                              | E 1/2                                 | F                                   |
| Lesco 705698 (pattern 0.25)   | 3 mph           | 7 feet               | 11                                   | 11 1/2                             | 13                                    | 14                                  |
| Lely Models WTR, WFR, HR, 1250<br>(PTO at 450 rpm) Pattern III-C                      | 4.5 mph         | 32 feet              | 4 1/4                                | 5 1/2                              | 6                                     | 6 1/2                               |
| Vicon (03 Series)   | 4.5 mph         | 28 feet              | 18                                   | 23                                 | 27                                    | 31                                  |



**10005125** (AGC23UFE5.40)