# Andersons Golf Products Turf Fertilizer 24-0-18

- Contains MUtech®-XL for extended feeding
- Contains potassium sulfate

# **Guaranteed Analysis**

Total Nitrogen (N)	24.00%
2.73% Urea Nitrogen	
16.89% Water Insoluble Nitrogen	
4.38% Other Water Soluble Nitrogen*	
Soluble Potash (K <sub>2</sub> O)	18.00%
Sulfur (S)	6.12%
6.12% Combined Sulfur (S)	

Derived from ureaform and potassium sulfate.

### F002091

Information regarding the contents and levels of metals in this product is available on the internet at http://www.aapfco.org/metals.html

### **DIRECTIONS FOR USE**

Apply only as directed. Apply during the growing season. Andersons Golf Products Turf Fertilizer 24-0-18 supplies a high level of nitrogen and potassium for soils low in these nutrients. Adequate potassium levels help promote root development and resistance to stress.

**Nitrogen Notice:** For those states with nitrogen application restrictions, including but not limited to MD, NH, NJ, PA and VA, do not apply more the 2.9 lbs. of this product per 1,000 sq.ft.

## **Application Rates:**

LOW: 2.1 lbs/1,000 sq. ft. MEDIUM: 3.2 lbs/1,000 sq. ft. HIGH: 4.2 lbs/1,000 sq. ft.

### For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- Apply at the LOW to MEDIUM RATES when temperatures exceed 85°F.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

### STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

# IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

# WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

### **LEGAL RIGHTS:**

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

MUtech and Season Long are registered trademarks of The Andersons, Inc.

### Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration.

Please calibrate your spreader prior to applying product.

50 lbs. feeds 23,800 sq. ft. (0.55 acre) with 0.50 lbs. N/1,000 sq. ft. at the LOW RATE

50 lbs. feeds 15,600 sq. ft. (0.36 acre) with 0.76 lbs. N/1,000 sq. ft. at the MEDIUM RATE

50 lbs. feeds 11,900 sq. ft. (0.27 acre) with 1.00 lbs. N/1,000 sq. ft. at the HIGH RATE

			SPREADER SETTINGS		
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LOW RATE 2.1 lbs/1,000 sq. ft.	MEDIUM RATE 3.2 lbs/1,000 sq. ft.	HIGH RATE 4.2 lbs/1,000 sq. ft.
Andersons AccuPro 2000, SR-2000 (cone 7)	3 mph	10 feet	J 3/4	K 3/4	M 1/4
Scotts R-8, R-8A (cone 7)	3 mph	10 feet	I	J 1/2	K 1/2
Lesco 020093 (pattern 0.25)	3 mph	8 feet	C 1/2	D 1/2	E
Lesco 705698 (pattern 0.25)	3 mph	8 feet	9	11	12
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern III-C	4.5 mph	30 feet	4	4 3/4	5 1/2
Vicon (03 Series)	4.5 mph	25 feet	16	21	26

SGN 150 Net Wt. 50 Lbs. (22.68 kg)





10005135

<sup>\*4.38%</sup> Slowly available nitrogen from ureaform.