

Andersons Golf Products

Turf Fertilizer

28-3-10

- Contains NS-54™ nitrogen to provide uniform growth with extended nitrogen feeding.
- Potassium supplied by potassium sulfate.
- SGN 215 for use on fairways, roughs and other turf areas.

Guaranteed Analysis	
Total Nitrogen (N)	28.00%
1.17% Ammoniacal Nitrogen	
26.83% Urea Nitrogen*	
Available Phosphate (P ₂ O ₅)	3.00%
Soluble Potash (K ₂ O)	10.00%
Sulfur (S)	5.89%
2.49% Free Sulfur (S)	
3.40% Combined Sulfur (S)	

Derived from diammonium phosphate, potassium sulfate and polymer coated sulfur coated urea.

*26.83% Slowly available urea nitrogen from polymer coated sulfur coated urea.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.html>

DIRECTIONS FOR USE
Apply only as directed during the growing season.

Application Rates:
LOW: 2.7 lbs/1,000 sq. ft.
MEDIUM: 3.5 lbs/1,000 sq. ft.

FLORIDA APPLICATIONS:
We recommend that you follow the Florida Green Industries BMP's at:
<http://www.flrules.org/Gateway/reference.asp?No=Ref-04706>

We recommend that you follow the Florida Golf Course BMP's at:
<http://www.flrules.org/Gateway/reference.asp?No=Ref-04702>

- For all applications:**
- Apply to dry foliage.
 - Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
 - Do not collect clippings for at least one mowing following application to avoid particle pick-up.

- Cool Season Grasses:**
- Apply at the MEDIUM RATE in the spring and fall months.
 - Apply at the LOW RATE in the summer months or when temperatures exceed 85°F.
- Warm Season Grasses:**
- Apply at the MEDIUM RATE during the growing season.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

STORAGE AND USE
Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:
Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:
Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:
THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

NS-54 is a trademark of The Andersons, Inc.

Suggested Spreader Settings				
These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product. 50 lbs feeds 18,500 sq. ft. (0.43 acre) with 0.75 lbs. N/1,000 sq. ft. at the LOW RATE 50 lbs feeds 14,200 sq. ft. (0.33 acre) with 0.98 lbs. N/1,000 sq. ft. at the MEDIUM RATE				
SREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS	
			LOW RATE 2.7 lbs/1,000 sq. ft.	MEDIUM RATE 3.5 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 4); Andersons 2000 SR / SR-2000 (cone 4)	3 mph	11 feet	K 3/4	L 1/4
Scotts R-8, R-8A (cone 4)	3 mph	11 feet	J	K
Lesco 020093 (pattern 0.25)	3 mph	8 feet	D 1/2	E 1/2
Lesco 705698 (pattern 0.25)	3 mph	8 feet	11	13
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-C	4.5 mph	38 feet	5	5 1/2
Vicon 03 Series	4.5 mph	28 feet	24	28

SGN 215

Net Wt. 50 Lbs. (22.68 kg)



10005150 (AGC28265.40)