

The Andersons Turf Products

Fertilizer

45-0-0

- Contains Fortify[®] 

Guaranteed Analysis

Total Nitrogen (N) 45.00%
45.00% Urea Nitrogen*

Derived from urea.

*45.00% nitrogen stabilized with N-(N-Butyl) thiophosphoric triamide and dicyandiamide.

F002091

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LIGHT RATE: 2.22 lbs/1,000 sq. ft.
LOW RATE: 2.78 lbs/1,000 sq. ft.
MEDIUM RATE: 3.33 lbs/1,000 sq. ft.
HIGH RATE: 3.89 lbs/1,000 sq. ft.

FLORIDA APPLICATIONS:

We recommend that you follow the Green Industries BMP's at:
http://fyn.ifas.ufl.edu/pdf/GIBMP_Manual_Web_English_2015.pdf

We recommend that you follow the Golf Course BMP's at:
<http://www.dep.state.fl.us/water/nonpoint/docs/nonpoint/glfbmp07.pdf>

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- Not recommended for use in spray tank applications.

Cool Season Grasses:

- Apply at the LOW or MEDIUM RATE every 6-8 weeks during the period of active growth.
- Apply at the LIGHT RATE when temperatures exceed 85°F.

Warm Season Grasses:

- Apply at the LOW to HIGH RATE every 4-6 weeks during the period of active growth.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent

to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

Fortify is a registered trademark of The Andersons, Inc.

Suggested Spreader Settings						
These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.						
50 lbs. feeds 22,500 sq. ft. (0.52 acres) with 1.00 lbs. N/1,000 sq. ft. at the LIGHT RATE						
50 lbs. feeds 17,900 sq. ft. (0.41 acre) with 1.25 lbs. N/1,000 sq. ft. at the LOW RATE						
50 lbs. feeds 15,000 sq. ft. (0.34 acre) with 1.50 lbs. N/1,000 sq. ft. at the MEDIUM RATE						
50 lbs. feeds 12,800 sq. ft. (0.29 acre) with 1.75 lbs. N/1,000 sq. ft. at the HIGH RATE						
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS			
			LIGHT RATE 2.22 lbs/1,000 sq. ft.	LOW RATE 2.78 lbs/1,000 sq. ft.	MEDIUM RATE 3.33 lbs/1,000 sq. ft.	HIGH RATE 3.89 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 4); Andersons 2000 SR / SR-2000 (cone 4)	3 mph	10 feet	K 1/4	K 3/4	L 1/4	L 3/4
Andersons LCO-1000	3 mph	10 feet	K 1/4	K 3/4	L 1/4	L 3/4
Scotts R-8, R-8A (cone 4)	3 mph	10 feet	I 3/4	J 3/4	K 1/4	K 3/4
Lesco 020093 (pattern 0.25)	3 mph	7 feet	D 1/2	D 3/4	E	E 1/4
Lesco 705698 (pattern 0.25)	3 mph	7 feet	11	11/12	12	12 1/2
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-C	4.5 mph	36 feet	4 3/4	5 1/4	5 1/2	6
Vicon (03 Series)	4.5 mph	28 feet	20	25	27	30

Net Wt. 50 Lbs. (22.68 kg)



10005643

J19